2-5000-15 Section S
Page 1

## Housewrap



REX ™ Wrap is a woven and coated polypropylene weather resistant barrier that provides air and moisture protection.

- Tiny micro perforations allow moisture vapor inside the wall cavity to escape, and prevents moisture condensation
- Light weight and easy to install
- Tear resistance reduces jobsite waste

- Meets or exceeds all building codes
- Custom print available at no additional cost (one pallet minimum)

## Shaded Items = Special Order

Item	Size	Rolls/Pallet	List/Roll
Rex9100	9 x 100'	50	92.25
Rex9150	9 x 150′	45	138.12
Rex9195	9 x 195'	40	179.73
Rex10100	10 x 100'	50	102.51
Rex10150	10 x 150'	45	153.75
Rex10195	10 x 195'	40	199.92

Bluebond Housewrap Tape						
Tano2220	3" x 330'	12 Rolls/Case	19.50/Roll			
Tape3330	3 X 33U	12 KUIIS/Case	234.00/Case			

While supplies last: receive a free applicator with each full case of Bluebond Housewrap Tape.



## **Roofing Underlayment**



SyntheticRoof Underlayment

www.alphaprotech.com

**TECHNOPLY** is a 100% synthetic woven roof underlayment offering high tear strengths, a proprietary walking surface and most important a green solution to today's ecological building technology. **TECHNOPLY** is the **GREEN** answer to 15# asphaltic felt paper.

- Manufactured from post industrial recycled materials.
- 100% recyclable eliminating job site scrap.
- 2.5 times lighter than 15# felt.
- 25 times stronger than 15# felt no job site blow offs.
- 25 year warranty to shed water.
- UV resistant and can be exposed for up to 6 months.
- 10 square rolls fewer rolls to carry on the roof.
- Pre-printed nailing pattern and overlap lines speeds installation.

Product Specifi	Test Method	
Roll Width	48 in.	
Roll Length	250 ft.	
Weight Per Square	2.0 lbs	
Nominal Thickness	7 Mils	ASTM D-1777
Water Transmission	Pass	ASTM D-4869
Tensile Strength		ASTM D-828
MD	57 lbs	
CD	57 lbs	
Tear Strength		ASTM D-4533
MD	36 lbs	
CD	36 lbs	
Pliability	Pass	ASTM D-226
Water Ponding	Pass	ASTM D-779

	TECHNOply™	15# Felt Paper
Composite Material	100% Polypropylene	Asphalt
Weight Per Roll	20 lbs	45 lbs
UV-Resistant	YES - Up to 6 months	No
Anti-Slip Surface	YES - Using advanced technology	No
Tear-Resistant	YES - 25x that of 15# Felt	No
Warranty	YES - 25 Years	No
Class A Fire Rated	YES - Offering better roof protection	No
Pre-Printed Nailing Pattern	YES	No
Roll Length	250 lineal feet	144 lineal feet
Roll Width	48 in.	36 in.

Item	Size	List/Roll
Techno	4' x 250' – 10 Squares	151.50

