





REX<sup>™</sup> SynFelt is a high strength woven synthetic roof underlayment that can save you 50% in labor and time expense, compared to 30# felt. Here's why:

- The most slip resistant underlayment in the industry.
- 20 times stronger than felt-won't tear-off or buckle when wet.
- 10X lighter per square and 20X stronger than 30# felt
- · 10 squares per roll weighing only 28 lbs
- UV resistant and can be exposed for up to 6 months
- Light gray color reduces heat and provides cooler working surface
- Pre-printed nailing pattern speeds installation

The smartest builders and roofers in America use REX™ SynFelt.

Product Specification		Test Method
Roll Width	48 in.	
Roll Length	250 ft.	
Weight Per Square	2.8 lbs	
Nail Seal Ability	Pass	ASTM D-1970
Water Transmission	Pass	ASTM D-4869
Tensile Strength		ASTM D-828
MD	96 lbs	
CD	116 lbs	
Tear Strength		ASTM D-4533
MD	58 lbs	
CD	77 lbs	
Pliability	Pass	ASTM D-226
Water Ponding	Pass	ASTM D-779

	REX™ SynFelt	30# Felt Paper
Composite Material	100% Polypropylene	Asphalt
Weight Per Roll	28 lbs	60 lbs
UV-Resistant	YES - Up to 6 months	No
Anti-Slip Surface	YES - Using advanced technology	No
Tear-Resistant	YES - 20x that of 30# Felt	No
Warranty	YES - 25 Years	No
Class A Fire Rated	YES - Offering better roof protection	No
Pre-Printed Nailing Pattern	YES	No
Roll Length	250 lineal feet	72 lineal feet
Roll Width	48 in.	36 in.

Alpha ProTech Engineered Products Inc. 301 South Blanchard St. Valdosta, GA 31601 866-312-1637 Nationwide Distributions Centers Valdosta, Georgia Janesville, Wisconsin Nogales, Arizona Salt Lake City, Utah

